



# SECTIONAL DOORS MODELS 2720/2700/1350





The Model 2720, 2700, and the 1350 are Amarr's top-of-the-line high R-Value Doors. Constructed using 2" or 1-3/8" foamed-in-place polyurethane insulation which creates a strong monolithic panel that is energy efficient. The Model 2720 has a 20-gauge steel front skin that provides a perfect option for heavy industrial applications.

Each model is secured with standard 14-gauge, galvanized steel hinges. The interior skin of each section has two continuous horizontal 20-gauge reinforcing strips. The section joint is thermally broken and chemically bonded with a pressure-sensitive adhesive sealant. An EPDM rubber weather seal further enhances the performance of the joint.

#### WARRANTIES

- 10-year Limited Warranty on the paint and finish
- 1-year Limited Warranty on hardware
- See your dealer or visit amarr.com for complete warranty details

COLORS Amarr steel doors arrive pre-painted; for custom colors, exterior latex paint must be used. Visit amarr.com for instructions on painting. Actual paint colors may vary from samples show







The Model 2700 and 1350 use a brighter tone of white color than the 2720

#### OPTIONAL PASS DOOR



Available for Model 2700 only in door sizes up to 16'2" wide x 16' tall. Wind Load option not available.

### Construction

### Model 2720

Extra Heavy-duty 2" 20 Gauge Foamed-in-Place Door

## Model 2700

Heavy-duty 2" Foamed-in-Place Door

### Model 1350 Heavy-duty 1-3/8" Foamed-in-Place Door

\*Based upon independent laboratory test results \*\*Calculated door section R-value is in accordance with DASMA TDS-163.



### TRIPLE-LAYER

Steel + Insulation + Steel

Track: All Amarr doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit www.amarr.com.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

OPTIONAL FULL-VIEW PANEL

24" x 6" DOUBLE INSULATED

ACRYLIC WINDOWS WITH BLACK FRAME

Clear and Dark Bronze Anodized Aluminum, White Powder Coat, or Custom Powder Coat colors. Not available for 1350.


### PANELS



RIBBED PANEL WITH STUCCO EMBOSSMENT 2720 is Flush Panel with stucco embossment

#### WINDOW OPTIONS







24" X 12" INSULATED GLASS Available with either a black or white frame

Entrematic reserves the right to change specifications and designs without notice and without incurring obligations. Sectional door products from Entrematic may be the

ore U.S. and/or foreign, issued and/or



pending, design and/or utility patents

165 Carriage Court Winston-Salem, NC 27105 800.503.DOOR www.amarr.com

FOR PRODUCT BINDER: 1.866.366.4814 FOR TECHNICAL QUESTIONS: 1.866.366.4814



Amarr as word or logo is a registered trademark belonging to Entrematic Group AB or other companies controlled by the same organization. All rights reserved. ©Entrematic Group AB 2014. All rights reserved. Printed in USA Form #6211114/10M/GVS







